



Manager IQ Easy

1030000000 - 24 V DC powered
1030000010 - 100-240 V AC powered


Connector IQ M12 male angled
5 pole (screw connections)
7519020357 - \varnothing 4-6 mm cables
7519020358 - \varnothing 6-8 mm cables

Sub-D connector
male 25 pole
P/N 3900236025

Power cord IEC-C13
2 m, with lock
P/N 9146340700


24V power connector
for \varnothing 4 - 6,5mm cables
P/N 9370000205

Cord IQ interconnection M8
female-male straight 3 pole
7519020291 - 5 m
7519020292 - 10 m
7519020294 - 25 m



Extension IQ Easy


1030000100 - 24 V DC powered
1030000110 - 100-240 V AC powered



Cord device M12 female angled 5 pole
7519020375 - 5 m, unshielded
7519020376 - 10 m, unshielded




Cord device M12 female straight 5 pole
7519020365 - 5 m, unshielded
7519020366 - 10 m, unshielded
7519020380 - 10 m, cable chain, shielded



Connector device M12 female angled
5 pole (screw connections)
7519020355 - \varnothing 4-6 mm cables
7519020356 - \varnothing 6-8 mm cables



Connector IQ M12 male straight
5 pole (screw connections)
7519020352 - \varnothing 4-6 mm cables
7519020353 - \varnothing 6-8 mm cables



Connector device M12 female straight
5 pole (screw connections)
7519020350 - \varnothing 4-6 mm cables
7519020351 - \varnothing 6-8 mm cables



Cord device M12 female-male straight 5 pole
7519020390 - 2 m, unshielded
7519020391 - 5 m, unshielded
7519020392 - 10 m, unshielded
7519020386 - 5 m, cable chain, unshielded
7519020387 - 10 m, cable chain, unshielded
7519020383 - 5 m, cable chain, shielded
7519020384 - 10 m, cable chain, shielded



 An ITW Company www.simco-ion.nl Tel: +31 (0)573 288333	Name: Manager/Extension IQ Easy overview connections				Drawn: AB	Part no.: -
	CAD generated NOT updated	Dimensions in mm	Date: 6-2-2014	A3 M: -	ECN-	Check: -